

LUBEX PRIMUS SVW-LA 0W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is the high performance fully synthetic motor oil which is developed with Low-SAPS formulation for specially vehicles of Volkswagen group (VW, Porsche, Audi, Skoda, Seat) that have low emission systems (DPF, GPF, TWC). It is suitable for use in gasoline, passenger diesel and light commercial vehicles.

APPLICATION/ USAGE

It is suitable for use in passenger cars that meet Euro 4, 5 and 6 emission standard requirements. It can be used with all diesel particulate filter, natural aspiration, pump-diesel injector, turbo-charged and multi-valve engines without any problem.

ADVANTAGES/ BENEFITS

- Prolongs the life of exhaust emission systems and protects the environment due to its low ash, phosphorus and sulphur contents.
- Provides up to 1.7% fuel savings due to low friction and oxidation performance.*
- Provides excellent protection against wear and corrosion since it is produced with low friction technology.
- Has high oxidation resistance and long drain intervals since it is produced with high technology synthetic base oils and high performance additives,
- Provides high protection against the formation of soot and sediment due to its excellent cleaning power.
- Provides constant lubrication in all climate and road conditions. Especially in winter, it provides easy operation of the engine with low viscosity.
- It is produced with Low Friction Technology and thanks to its high viscosity index, it creates a

durable oil film at any temperature and minimizes the level of wear occurring during engine start-up and heating.

- With the help of detergent-dispersing additives it contains, it dissolves the contamination caused by combustion in the environment and prevents accumulation of sediment. Increases the motor performance by keeping the lubrication channels clean.

SPECIFICATIONS/ APPROVALS

API SN
ACEA C3
PORSCHE C-30
VW Standard 504 00 and VW Standard 507 00

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr

| TECHNICAL PROPERTIES | TYPICAL VALUES | TEST METHOD |
|------------------------------------|----------------|-------------|
| SAE Viscosity Class | 0W-30 | - |
| Density (15°C, g/cm ³) | 0,842 | ASTM D 4052 |
| Kinematic Viscosity (100°C, cSt) | 12 | ASTM D 445 |
| Viscosity Index | 175 | ASTM D 2270 |
| Flash Point (°C, min) | 215 | ASTM D 92 |
| Pour Point (°C) | -45 | ASTM D 97 |
| TBN (mgKOH/g) | 8,2 | ASTM D 2896 |
| CCS (-35°C, cP) | 5800 | ASTM D 5293 |
| Sulphated Ash (%wt) | 0,78 | ASTM D 874 |
| HTHS (150°C, cP) | 3,6 | ASTM D 4741 |

*According to comparing the results of ACEA M111 fuel economy with reference oil at industrial standards.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr