

LUBEX PRIMUS PG-LA 5W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is the high performance fully synthetic motor oil which has Low-SAPS (Low-Sulfated Ash, Phosphorus and Sulfur) technology and developed especially for passenger cars and light commercial PSA group vehicles with diesel particle filter (DPF).

APPLICATION/ USAGE

It is suitable for use in all passenger cars that meet Euro 4 and 5 emission standards. It can be used in all natural aspirated, diesel particle filter, pump-diesel injector, turbocharged and multi-valve engines operating with gasoline, passenger diesel and LPG.

It is specifically developed for Peugeot-Citroën and Fiat vehicles with Diesel Particulate Filter.

ADVANTAGES/ BENEFITS

- Extends the life of exhaust emission systems (DPF) and protects the environment with its low ash, phosphorus and sulfur content.
- Provides fuel saving up to 1.7% due to its low friction performance.*
- Provides excellent protection against rust and corrosion in the engine.
- It is produced with Low Friction Technology and thanks to its high viscosity index, it creates a durable oil film at any temperature and minimizes the level of wear occurring during engine start-up and heating.
- Has superior piston cleaning performance providing excellent protection against cylinder polishing and wear.

- With the help of the detergent-dispersant additives it contains, it prevents the accumulation of sediment by dispersing the dirt formed as a result of combustion and increases the engine performance.
- Has the ability to control oil thickening caused by soot formation.
- Provides long drain intervals by increasing oxidation resistance of the oil thanks to its high-tech synthetic oils and high performance additives.

SPECIFICATIONS/ APPROVALS

API SN
ACEA C2, C3
FIAT 9.55535-S1
PSA B71 2290

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	5W-30	-
Density (15°C, g/cm ³)	0,848	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	10,0	ASTM D 445
Viscosity Index	170	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-42	ASTM D 97
TBN (mgKOH/g)	7,1	ASTM D 2896
CCS (-30°C, cP)	4400	ASTM D 5293
Sulphated Ash (%wt)	0,77	ASTM D 874
HTHS (150°C, cP)	3,6	ASTM D 4741

*According to comparing the results of ACEA M111 fuel economy with reference oil at industrial standards.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr