

# LUBEX PRIMUS FM-LA 0W-30

## HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

### PRODUCT DESCRIPTION

It is a high performance synthetic engine oil developed by using specially selected fully synthetic base oils and high technology additives.

### APPLICATION/ USAGE

It has been specially developed for use in FIAT's new generation 1.3 Multijet Euro 6 (Adblue/Selective Catalytic Reduction-SCR) passenger and light commercial diesel engines requiring FIAT 9.55535-DM1 specification. It is also suitable for use in low emission passenger and light commercial diesel engines where ACEA C5 performance level and SAE 0W-20 viscosity grade engine oil is required.

### ADVANTAGES/ BENEFITS

- Even at coldest start-up conditions it prevents metal-metal contact and minimize wear by building a stable oil film with its excellent flow performance.
- Owing to its low viscosity characteristic and low friction feature, it helps to achieve lower emission by providing fuel economy.
- It extends engine life by providing excellent protection against deposit and soot formation with its superior cleaning performance.
- It is manufactured with mid-SAPS (sulfated ash, phosphorus and sulfur) technology for diesel particulate filter (DPF) engines in order to reduce harmful exhaust emissions. It extends the life of the

exhaust emission system and protects the environment.

- It protects the engine against corrosion with its specially selected additives by neutralizing the acidic by-products formed as a result of combustion.
- Its high oxidation and thermal stability enables to prevent the formation of deposits in the engine and provide superior protection without compromising lubrication performance during the long oil change interval.

### SPECIFICATIONS/ APPROVALS

ACEA C2  
FIAT WSS-M2C950-A  
Jaguar / Land Rover STJLR.03.5007

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	0W-30	-
Density (15°C, g/cm <sup>3</sup> )	0,844	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	9,8	ASTM D 445
Viscosity Index	200	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-45	ASTM D 97
TBN (mgKOH/g)	8,0	ASTM D 2896
CCS (-35°C, cP)	5383	ASTM D 5293
HTHS (150°C, cP)	3,1	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

02.2022.10.12



**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr