

LUBEX PRIMUS RN 5W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is the fully synthetic motor oil that ensures optimum performance for Renault group vehicles by providing superior protection and lubrication in harsh driving conditions and operating temperatures.

APPLICATION/ USAGE

It is suitable for use in all kinds of modern technology passenger cars. It can be used in all natural aspirated, injection, turbocharged and multi-valve engines operating with gasoline, passenger diesel and LPG.

ADVANTAGES/ BENEFITS

- Minimizes wear with excellent flow performance at engine start-up, even at low temperatures.
- Provides excellent engine protection against deposits and soot formation by its high cleaning power.
- Provides unique protection against wear and corrosion in engines and its components.
- It is produced with Low Friction Technology and thanks to its excellent fluidity performance; it creates a durable oil film at every temperature, increases the engine performance by providing maximum efficiency from the fuel and contributes to fuel economy.
- With the help of detergent-dispersant additives, it prevents the accumulation of deposits by

dispersing the dirt formed as a result of combustion, increases the motor performance by ensuring that the lubrication channels remain clean and prolongs the life of motor.

SPECIFICATIONS/ APPROVALS

API SL*/CF
ACEA A3/B4
RENAULT RN 0700, RN 0710

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

| TECHNICAL PROPERTIES | TYPICAL VALUES | TEST METHOD |
|------------------------------------|----------------|-------------|
| SAE Viscosity Class | 5W-30 | - |
| Density (15°C, g/cm ³) | 0,852 | ASTM D 4052 |
| Kinematic Viscosity (100°C, cSt) | 11,4 | ASTM D 445 |
| Viscosity Index | 175 | ASTM D 2270 |
| Flash Point (°C) | 210 | ASTM D 92 |
| Pour Point (°C) | -42 | ASTM D 97 |
| TBN (mgKOH/g) | 11,5 | ASTM D 2896 |
| CCS (-30°C, cP) | 5000 | ASTM D 5293 |
| HTHS (150°C, cP) | 3,8 | ASTM D 4741 |

*API SN Engine Test Requirement

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr