

# LUBEX PRIMUS MV 0W-30

## HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

### PRODUCT DESCRIPTION

It is the fully synthetic motor oil which is produced with special selected synthetic base oils and additive technology and suitable for use in gasoline, passenger diesel and light commercial vehicles.

### APPLICATION/ USAGE

It is suitable for especially the new generation engines developed by European motor manufacturers and many model vehicles with all natural aspiration, direct injection, turbo-charged and multi-valve engines operating with petrol and diesel.

### ADVANTAGES/ BENEFITS

- Minimizes wear with its excellent flow performance during the first run of engine even at low temperatures.
- Provides excellent engine protection against the formation of soot and sediment due to its excellent cleaning power.
- Provides constant lubrication at all types of weather and road conditions therefore it can be used safely in four seasons.
- Protects the engine against wear and corrosion by creating a durable oil film at very low or very high temperatures thanks to its special additives it

contains.

- It has low oil consumption due to its perfect viscosity control and increase the engine performance by maximizing full efficiency.

### SPECIFICATIONS/ APPROVALS

API SL\*/CF  
ACEA A3/B4  
MB 229.3  
RN 0710, RN 0700  
VW 502.00 / 505.00  
BMW LL-98  
GM LL-B-025

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

| TECHNICAL PROPERTIES               | TYPICAL VALUES | TEST METHOD |
|------------------------------------|----------------|-------------|
| SAE Viscosity Class                | 0W-30          | -           |
| Density (15°C, g/cm <sup>3</sup> ) | 0,846          | ASTM D 4052 |
| Kinematic Viscosity (100°C, cSt)   | 11,1           | ASTM D 445  |
| Viscosity Index                    | 175            | ASTM D 2270 |
| Flash Point (°C)                   | 215            | ASTM D 92   |
| Pour Point (°C)                    | -45            | ASTM D 97   |
| TBN (mgKOH/g)                      | 10,5           | ASTM D 2896 |
| CCS (-35°C, cP)                    | 5900           | ASTM D 5293 |
| HTHS (150°C, cP)                   | 3,5            | ASTM D 4741 |

\*Meets API SN Engine Test Requirement

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.10.27



**BELGiN**

BELGiN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr