

LUBEX PRIMUS EC 10W-40

HIGH PERFORMANCE MOTOR OIL

PRODUCT DESCRIPTION

It is the high performance, synthetic technology motor oil that provides superior protection and cleaning under extreme driving conditions. It is suitable for use in gasoline, passenger diesel and light commercial vehicles. It is produced by blending high-tech mineral and synthetic base oils with special additives.

APPLICATION/ USAGE

It is suitable for use in gasoline and diesel engines of passenger and light commercial vehicles. It can be used with motors of all modern technology vehicles that have injection, turbocharged and multi valve without any problem.

ADVANTAGES/ BENEFITS

- Provides constant lubrication in all climate and road conditions. Therefore it can be used safely in all four seasons.
- Provides low oil consumption by its perfect viscosity control.
- Protects the engine against rust and corrosion.

- Prevents accumulation of ash and residue in the engine by its special additives. It improves performance and prolongs life of engine by keeping the critical components of engine clean.
- Minimizes the wear on motor during start-up and warm-up by providing a durable oil film at any temperature and climate conditions.

SPECIFICATIONS/ APPROVALS

API SL/CF

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-40	-
Density (15°C, g/cm ³)	0,897	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14,55	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C)	220	ASTM D 92
Pour Point (°C)	-30	ASTM D 97
TBN (mgKOH/g)	6,7	ASTM D 2896
CCS (-25°C, cP)	5900	ASTM D 5293

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

02.2021.03.11



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr