

LUBEX RAPIDUS FS 10W-40

HIGH-TECH FULL SYNTHETIC MOTORCYCLE OIL

Product Description

High-tech full synthetic motorcycle oil, formulated to provide full responsiveness from the engine and superior protection for all 4-stroke modern motorcycles.

Application/Usage

It can be used safely in high performance motorcycles.

Advantages/Benefits

- Provides minimum vibration and noise due to excellent viscosity stability,
- Provides smoother clutch coupling and gear change due to low friction and oxidation performance,
- Enhanced responsiveness and efficient power delivery in the engine by excellent lubrication performance, especially at high operating temperatures,
- Provides constant lubrication in any road and climate conditions so it can be used in four seasons. Especially in winter, allows easy operation of the engine and minimize wear,
- Protects engine against corrosion, oxidation and formation of foam,
- Provides high performance in air-cooled and water cooled engines,
- Has a high viscosity index value and contains exclusive additives which protects the engine and prolongs its life,

- In virtue of its detergent/dispersant additives, it cleans up the engine,
- Improves engine performance by providing maximum efficiency,
- Has low oil consumption in virtue of its excellent viscosity control,
- Increase engine performance by providing maximum fuel efficiency,
- Has the ability to control of oil thickening caused by soot formation.

Specifications/Approvals

API SN/CF,
JASO MA2

Storage

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-40	-
Kinematic Viscosity (100°C, cSt)	14,8	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C, min)	220	ASTM D 92
Pour Point (°C)	-27	ASTM D 97
TBN (mgKOH/g)	7,0	ASTM D 2896

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2013.04.10

Belgin Madeni Yağlar Tic. ve San. A.Ş.

Gebze OSB Mah. İhsan Dede Cad. No: 125/1 41400 Gebze/Kocaeli/Turkey

Tel: +90 262 751 02 92 – Fax: +90 262 751 01 98

info@belginoil.com – www.belginoil.com