

LUBEX AGROS UTTO 82 TRANSMISSION OIL

PRODUCT DESCRIPTION

It was formulated with high quality solvent refined paraffinic mineral oil containing extreme pressure additives and friction modifiers for transmissions, final drives and hydraulic systems of farm and industrial tractors and mobile equipment including those with oil immersed disc brakes.

APPLICATION/USAGE

It is recommended for service top-up and refill of transmissions, differentials, final drives, hydraulic and power steering systems - and also for fluid immersed disc brakes in agricultural and industrial tractors and similar mobile equipment.

ADVANTAGES/BENEFITS

- Has high heat resistance and makes lubrication at high temperatures. It provides power transmission at low temperatures.
- Has a high viscosity index value and contains exclusive additives which protects the engine and prolongs its life.
- Prevents rust and corrosion and reduces any tendency towards the formation of foam which can promote cavitation, noisy pump operation and increased wear.
- In virtue of its detergent/dispersant additives, it cleans up the engine.
- Has low oil consumption in virtue of its excellent viscosity control.
- Improves engine performance by providing maximum efficiency.

SPECIFICATIONS/APPROVALS

API GL-4
 JI CASE: MS 1204-MS 1205-MS 1206-MS 1207-MS 1210
 JOHN DEERE: JDM J20C / J20D
 NEW HOLLAND: FNHA-2-C201.00
 FORD: M2C134-A/B/C/D M2C86-B/C
 MASSEY FERGUSSON: M1141-M1135-M1143-M1145
 WHITE FARM: Q-1826
 ALLISON: C-3 / C-4
 CATERPILLAR TO-2
 VOLVO: WB-101
 KUBOTA UDT
 EATON VICKERS
 ZF-TE-ML 03E/03F/05F/06E/06F/06K/17E/21F

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TEST VALUES	TEST METHOD
SAE Viscosity Class	10W-30	-
Appearance	Dark Yellow, Clear	-
Density (20°C) (g/cm ³)	0,866	ASTM D 1218
Kinematic Viscosity (100°C, cSt)	9,3-12,5	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C, min)	220	ASTM D 92
Pour Point (°C)	-30	ASTM D 92

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2021.05.03



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
 Gebze OSB Mah. İhsan Dede Cad.
 No: 125/1, 41400 Gebze, Kocaeli, Turkey
 T +90 262 751 02 92 F +90 262 751 01 98
 info@lubex.com.tr - lubex.com.tr