

LUBEX PRIMUS EC 20W-50

HIGH PERFORMANCE MOTOR OIL

PRODUCT DESCRIPTION

It is motor oil which was formulated with high quality mineral base oils and superior additive technology. It is especially suitable for use in high mileage gasoline, LPG, passenger diesel and light commercial vehicles.

APPLICATION/ USAGE

It works without any problem in all climate and road conditions. It can be easily used in gasoline, LPG and diesel engines of all light commercial and passenger vehicles.

ADVANTAGES/ BENEFITS

- Provides constant lubrication in all climate and road conditions. Therefore it can be used safely in all four seasons.
- Provides low oil consumption by its perfect viscosity control.
- Protects the engine against rust and corrosion.
- Prevents accumulation of ash and residue in the engine by its special additives. It improves

performance and prolongs life of engine by keeping the critical components of engine clean.

- Minimizes the wear on motor during start-up and warm-up by providing a durable oil film at any temperature and climate conditions.

SPECIFICATIONS/ APPROVALS

API SL/CF

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

| TECHNICAL PROPERTIES | TYPICAL VALUES | TEST METHOD |
|------------------------------------|----------------|-------------|
| SAE Viscosity Class | 20W-50 | - |
| Density (15°C, g/cm ³) | 0,891 | ASTM D 4052 |
| Kinematic Viscosity (100°C, cSt) | 18,6 | ASTM D 445 |
| Viscosity Index | 120 | ASTM D 2270 |
| Flash Point (°C) | 220 | ASTM D 92 |
| Pour Point (°C) | -24 | ASTM D 97 |
| TBN (mgKOH/g) | 6,8 | ASTM D 2896 |
| CCS (-15°C, cP) | 8600 | ASTM D 5293 |

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

02.2021.03.11



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr