

LUBEX PRIMUS FM 5W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is a fully synthetic motor oil that helps Ford vehicles perform optimally under difficult driving conditions.

APPLICATION/ USAGE

It has been developed especially for Ford brand vehicles that require engine oil to be used in the new generation Ford WSS-M2C913-D performance level. In addition, it is suitable for the use of all gasoline, passenger diesel and light commercial vehicles designed for low viscosity (HTHS) engine oil use. Also it can be used in Ford Transit brand vehicles with Diesel Particulate Filter (DPF) and without Diesel Particulate Filter (without DPF) where Ford WSS-M2C913-B, C and D approvals are required.

ADVANTAGES/ BENEFITS

- Thanks to its low friction technology and excellent flow and pumpability, it ensures a minimum level of wear during engine start-up and warm-up.
- Provides superior protection with excellent flow performance in start-stop motors.
- Provides fuel saving by its low friction performance.
- With the help of detergent-dispersing additives it contains, it dissolves the contamination caused by combustion in the environment and prevents

accumulation of sediment. Increases the motor performance by keeping the lubrication channels clean.

- Increases engine performance by maximizing fuel efficiency.
- Due to the synthetic oils it contains, it has a very long life and prolongs the oil change periods.

SPECIFICATIONS/ APPROVALS

API SL/CF
ACEA A5/B5
Ford WSS-M2C913-A-B-C-D

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	5W-30	-
Density (15°C, g/cm ³)	0,848	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	11,2	ASTM D 445
Viscosity Index	165	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-42	ASTM D 97
TBN (mgKOH/g)	9,6	ASTM D 2896
CCS (-30°C, cP)	5100	ASTM D 5293
Sulphated Ash (%wt)	1,2	ASTM D 874
HTHS (150°C, cP)	3,3	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021.10.27



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr