

LUBEX PRIMUS MV 5W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is the fully synthetic motor oil which is produced with special selected synthetic base oils and additive technology and suitable for use in gasoline, passenger diesel and light commercial vehicles.

APPLICATION/ USAGE

It is suitable for especially the new generation engines developed by European motor manufacturers and many model vehicles with all natural aspiration, direct injection, turbo-charged and multi-valve engines operating with petrol and diesel.

ADVANTAGES/ BENEFITS

- Minimizes wear with its excellent flow performance during the first run of engine even at low temperatures.
- Provides excellent engine protection against the formation of soot and sediment due to its excellent cleaning power.
- Provides constant lubrication at all types of weather and road conditions therefore it can be used safely in four seasons.
- It creates a durable oil film even at very low or very high temperatures and thanks to its special additives protects the engine against corrosion and wear.
- Provides low oil consumption due to its excellent viscosity control and increases the motor performance by maximizing fuel efficiency.

- With the help of detergent-dispersing additives, it prevents the accumulation of sediment by dispersing the impurities resulting from combustion in the environment and keeps the lubrication channels continuously clean and improves the engine performance.
- Provides excellent engine protection against sediment and soot formation with its superior cleaning power.

SPECIFICATIONS/ APPROVALS

API SL*/CF
ACEA A3/B4
BMW LL-98
GM LL-B-025
MB 229.5
Renault RN 0710, RN 0700
VW 502.00 / 505.00
*API SN Engine Test Requirement

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	5W-30	-
Density (15°C, g/cm ³)	0,851	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	11,0	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-39	ASTM D 97
TBN (mgKOH/g)	10,1	ASTM D 2896
CCS (-30°C, cP)	4700	ASTM D 5293
HTHS (150°C, cP)	3,5	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021 10.27

BELGiN

BELGiN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr