

## LUBEX PRIMUS PG-LA 0W-30

### HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

#### PRODUCT DESCRIPTION

It is a fully synthetic new generation high performance engine oil which is manufactured by blending synthetic base oils and high technology additives.

#### APPLICATION/ USAGE

It has been specially developed to meet PSA B71 2312 performance level which is required for the new generation PSA (Peugeot-Citroën) Group's Euro 6 Puretech and Blue HDI series engines with Selective Catalytic Reduction (SCR) and Diesel Particulate Filter (DPF). It is also suitable for use in passenger and light commercial diesel engines where SAE 0W-30 and ACEA C2 performance level engine oil is recommended.

#### ADVANTAGES/ BENEFITS

- It is manufactured with mid-SAPS (sulphated ash, phosphorus and sulfur) technology to be compatible with exhaust emission systems (DPF, SCR and TWC etc.) in order to extend their life and increase the efficiency.
- Owing to its low viscosity characteristic and low friction feature, it helps to achieve lower emission by providing fuel economy.
- Provides excellent protection against rust and corrosion in the engine.
- Even at coldest start-up conditions it prevents metal-metal contact and minimizes wear by building a stable oil film with its excellent flow

performance.

- Owing to its high oxidation and thermal stability, it prevents the formation of deposits in the engine and provides superior protection without compromising lubrication performance during the long oil change interval.

#### SPECIFICATIONS/ APPROVALS

ACEA C2  
PSA B71 2312

#### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

#### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	0W-30	-
Density (15°C, g/cm <sup>3</sup> )	0,848	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	9,8	ASTM D 445
Viscosity Index	169	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-45	ASTM D 97
TBN (mgKOH/g)	6,5	ASTM D 2896
CCS (-35°C, cP)	5686	ASTM D 5293
Sulphated Ash (%wt)	0,54	ASTM D 874
HTHS (150°C, cP)	3,2	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

02.2021.10.27



**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr