

LUBEX PRIMUS RN-LA 5W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is the fully synthetic motor oil especially developed for use in Renault vehicles with diesel particulate filter (DPF). It has low SAPS (low ash, phosphorus and sulfur) technology and Renault approval.

APPLICATION/ USAGE

It is suitable for use in passenger cars that meet all Euro 4 and 5 emission standard requirements. It can be used with all natural aspiration, diesel particulate filter, pump-diesel injector, turbocharged and multi-valve engines working with diesel. It is especially developed for Renault vehicles with Diesel Particulate Filter.

ADVANTAGES/ BENEFITS

- By its low ash, phosphorus and sulfur (Low SAPS) property extends the life of exhaust emission systems (DPF) and protects the environment.
- Provides fuel saving up to 1.7% by its low friction and oxidation performance.*
- Provides unique protection against wear and corrosion in the engine and its components.
- It is produced with Low Friction Technology and thanks to its high viscosity index, it creates a durable oil film at any temperature and minimizes the level of wear occurring during engine start-up and heating.
- Minimizes evaporation loss and contributes to fuel economy.
- Increases engine performance by maximizing fuel efficiency.

- It has superior piston cleaning performance which provides excellent protection against cylinder polishing and wear.
- Due to the synthetic oils it contains, it has a very long life and prolongs the oil change periods.
- It prevents the accumulation of sediment by dispersing the contamination caused by combustion in the environment with the help of detergent-dispersing additives in its content.

SPECIFICATIONS/ APPROVALS

ACEA C4
Jaguar / Land Rover STJLR.03.5005
RENAULT RN 0720

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	5W-30	-
Density (15°C, g/cm ³)	0,846	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	11,7	ASTM D 445
Viscosity Index	175	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-42	ASTM D 97
TBN (mgKOH/g)	8,1	ASTM D 2896
CCS (-30°C, cP)	4900	ASTM D 5293
HTHS (150°C, cP)	3,6	ASTM D 4741

*According to comparing the results of ACEA M111 fuel economy with reference oil at industrial standards.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

05.2022.10.12



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr