

# LUBEX PRIMUS SV-LA 0W-20

## HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

### PRODUCT DESCRIPTION

It is the high performance fully synthetic motor oil which is designed to provide fuel economy and long life for the new generation motors of Volkswagen group (VW, Porsche, Audi, Skoda, Seat) which are required 0W-20 viscosity grade and VW 508.00 / 509.00 specifications.

### APPLICATION/ USAGE

It can be used without any problem at the motors of all modern technology vehicles with direct injection, turbocharged and multi-valve.

### ADVANTAGES/ BENEFITS

- Provides high protection for new generation of VW motors with high volume and low tolerances.
- Minimizes wear with its excellent flow performance during the first run of engine even at low temperatures.
- Provides up to 4% fuel savings due to low friction and oxidation performance.\*
- Increases the engine performance and provides fuel economy by minimizing wear at every temperature with its high technology.
- Provides excellent protection against corrosion and wear.
- Minimize wear by creating a durable oil film in the engine at every temperature thanks to its high viscosity index.

- With the help of detergent-dispersing additives it contains, it dissolves the contamination caused by combustion in the environment and prevents accumulation of sediment. Increases the motor performance by keeping the lubrication channels clean.

### SPECIFICATIONS/ APPROVALS

PORSCHE C-20  
VW Standard 508 00 and VW Standard 509 00

### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	0W-20	-
Density (15°C, g/cm <sup>3</sup> )	0,825	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	8,2	ASTM D 445
Viscosity Index	170	ASTM D 2270
Flash Point (°C, min)	220	ASTM D 92
Pour Point (°C)	-42	ASTM D 97
TBN (mgKOH/g)	8,2	ASTM D 2896
CCS (-35°C, cP)	3400	ASTM D 5293
Sulphated Ash (%wt)	0,8	ASTM D 874
HTHS (150°C, cP)	2,6	ASTM D 4741

\*According to comparing the results of ACEA M111 fuel economy with reference oil at industrial standards.

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

05.2023.11.23



**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr