

## LUBEX ROBUS KM 20W50

### HIGH PERFORMANCE MOTOR OIL

#### PRODUCT DESCRIPTION

It is heavy duty motor oil which is formulated by using high quality mineral base oils and special additive technology and has a wide usage in old model trucks, buses, trucks, construction machines, agricultural machines and generators.

#### APPLICATION/ USAGE

It is produced to use in all trucks, buses, minibuses and automobile diesel and gasoline engines and generators. In addition, it is suitable for diesel motors of agricultural machines such as sowing-planting machines and diesel irrigation pumps.

#### ADVANTAGES/ BENEFITS

- Provide constant lubrication in any road and climate conditions. It can be used four seasons.
- Contains anti-foaming and anti-corrosion additives so improves the performance of the engine without causing oil pressure drop and foam.
- Forms strong film layer at each temperature due to its high viscosity index.

- It improves performance and prevents the accumulation of sediment by dispersing impurities caused by combustion with the help of detergent-dispersant additives it contains. This ensures that the lubrication channels are constantly clean.
- Prolongs life and performance of the motor.

#### SPECIFICATIONS/ APPROVALS

API SC/CC  
MIL-L-2104 B

#### STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5) - (+40)°C.

#### HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	20W-50	-
Density (15°C) (g/cm <sup>3</sup> )	0,889	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	19,2	ASTM D 445
Viscosity Index	120	ASTM D 2270
Flash Point (°C)	230	ASTM D 92
Pour Point (°C)	-18	ASTM D 97
TBN (mgKOH/g)	5,1	ASTM D 2896
CCS (-15°C, cP)	8700	ASTM D 5293

"The above information is derived from our quality checks, Given values are typical of current production, While future production will conform to our specification, variations in these characteristics may occur, Quality Control Analysis Report for to learn properties of the product that is supplied can give, It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose, Due to continual product research and development, the information contained herein is subject to change without notification,"

02,2021,03,10



**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.  
Gebze OSB Mah. İhsan Dede Cad.  
No: 125/1, 41400 Gebze, Kocaeli, Turkey  
T +90 262 751 02 92 F +90 262 751 01 98  
info@lubex.com.tr - lubex.com.tr