

LUBEX ROBUS MASTER SCN 10W-40

HIGH PERFORMANCE FULLY SYNTHETIC DIESEL MOTOR OIL

PRODUCT DESCRIPTION

It is high performance fully synthetic heavy duty diesel engine oil that is particularly suitable for use on Scania Euro V vehicles and provides superior protection against wear and deposit formation and fuel economy.

APPLICATION/ USAGE

It is formulated especially for Scania trucks, lorries and buses and can be used in heavy duty vehicles that meet Euro V, Euro IV and older emission standards. It can be used in heavy duty construction machinery, diesel engines of trucks, lorries and buses, including turbo and supercharged light commercial vehicles (minibuses, vans etc.) and low emission diesel engines. It is suitable for use in all types of vehicles using low or high sulfur-containing fuel and in all known high-speed diesel engines.

ADVANTAGES/ BENEFITS

- Provides to drive longer and reduces maintenance cost by meeting extended drive intervals.
- Protects the engine against wear, corrosion and rust.
- Provides lower fuel consumption due to improved viscosity stability and low friction properties.
- Provides excellent motor protection against deposits and soot formation thanks to its superior cleaning performance. With the help of the detergent-dispersant additives it contains, it prevents the accumulation of sediment by dispersing the dirt formed as a result of combustion.
- It can be used safely in every road and climate conditions by providing constant lubrication.

- Due to improved viscosity stability, provides excellent protection against wear at engine start-up even at low temperatures.

SPECIFICATIONS/ APPROVALS

API CI-4
ACEA E7, E4
CES 20078-77
DAF EXTENDED DRAIN
DEUTZ DQC III-10
GLOBAL (JAMA) DHD-1
JASO DH-1
MTU TYPE 3
MACK EO-N
MAN M 3277
DTFR 15B120 (MB 228.5)
Renault RXD, RLD-2
Scania LDF-3
Volvo VDS-3

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-40	-
Density (15°C) (g/cm ³)	0,861	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	13,6	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C)	>225	ASTM D 92
Pour Point (°C)	-36	ASTM D 97
TBN (mgKOH/g)	15,5	ASTM D 2896
CCS (-25°C, cP)	5600	ASTM D 5293

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2023.11.20



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr