

LUBEX MITRAS ATF II

AUTOMATIC TRANSMISSION OIL

PRODUCT DESCRIPTION

It is the automatic transmission oil produced by blending high quality refined base oils and special additives.

APPLICATION/USAGE

It can be used in automatic transmissions of passenger cars and heavy duty vehicles, hydraulic steering and some hydraulic systems.

ADVANTAGES/BENEFITS

- Shows superior performance in hot and cold climatic conditions.
- Thanks to its special additives, improves equipment performance by minimizing the wear that may occur in automatic transmissions.
- Due to their thermal stability and high oxidation resistance they are long-life products.
- Thanks to the special additives it contains, it prevents the formation of sediment and does not foam.
- Protects gears against rusting and corrosion.
- Reduces maintenance cost and increases the reliability of the gearbox by reducing oil leakage, oil consumption and contamination.
- Provides long-term oil and equipment life with extended oil and filter change intervals.
- Reduces waste disposal costs by minimizing the frequency and amount of oil change due to its long life.

SPECIFICATIONS/APPROVALS

GM Dexron II-D
DTFR 13C100 (MB 236.1)
Ford - Mercon
GM Allison C3 – C4
Caterpillar TO-2
Denison HF-0
ZF TE-ML 02F, 03D, 17C
MAN 339 TYPE V1
MAN 339 TYPE Z1
Voith H55.6335.3X
ZF TE-ML 04D, 14A

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH and SAFETY

Mevcut bilgiler ışığında, amaçlanan yer ve belirtilen kullanım koşullarında kullanıldığında bu ürünün insan sağlığı üzerinde olumsuz etki yaratması beklenmemektedir. Kullanılmış ürün yakılmamalı, toprağa ve atık su kanallarına dökülmemelidir. Atık yağlar, Atık Yağların Kontrolü Yönetmeliği'ne göre kategorilerine ayrılarak bu yönetmelikte tanımlanmış özelliklerdeki lisanslı işletmeler kanalı ile bertaraf edilmelidir. Gerektiğinde lütfen Malzeme Güvenlik Formunu okuyunuz.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
Appearance	Red-Bright	-
Density (20°C, g/cm ³)	0,850	ASTM D 1298
Kinematic Viscosity (100°C, cSt)	7,5	ASTM D 445
Viscosity Index	160	ASTM D 2270
Flash Point (°C)	160	ASTM D 92
Pour Point (°C)	-40	ASTM D 97
Foam (24°C, Seq. I, ml)	50/0	ASTM D 892
Copper Corrosion (3 h, 100°C)	1b	ASTM D 130
Sulphated Ash (% , max)	0,2	ASTM D 874

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2023.12.28



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr