

LUBEX MITRAS ATF DX II

AUTOMATIC TRANSMISSION OIL

PRODUCT DESCRIPTION

It is the automatic transmission oil produced by blending high quality refined base oils and special additives.

APPLICATION/USAGE

It can be used in automatic transmissions of passenger cars and heavy duty vehicles, hydraulic steering and some hydraulic systems..

ADVANTAGES/BENEFITS

- Reduces wear, thus increases the equipment performance by increasing production capacity.
- Thanks to the special additives it contains, it prevents the formation of sediments and as a result of minimizing the deposits provides longer gear and bearing life.
- Long-life products due to their thermal stability and high oxidation resistance.
- Decreases oil change frequency, thus provides prolonged oil and equipment life; reduces waste disposal costs to a minimum.
- Reduces maintenance needs and increases the reliability of gearbox by reducing the oil leaks, oil

consumption and pollution.

- Does not foam due to the antifoam additives unless there are mechanical problems in the system, prevents cavitations in the pumps.

SPECIFICATIONS/APPROVALS

GM Dexron II-D
GM Dexron II-E
GM Type A Suffix A

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

| TECHNICAL PROPERTIES | TYPICAL VALUES | TEST METHOD |
|------------------------------------|----------------|-------------|
| Appearance | Red-Bright | - |
| Density (20°C, g/cm ³) | 0,870 | ASTM D 1298 |
| Kinematic Viscosity (100°C, cSt) | 7,5 | ASTM D 445 |
| Viscosity Index | 160 | ASTM D 2270 |
| Flash Point (°C) | 190 | ASTM D 92 |
| Pour Point (°C) | -40 | ASTM D 97 |
| Foam (24°C, Seq. I, ml, max) | 50/0 | ASTM D 892 |
| Copper Corrosion (3 h, 100°C, max) | 1b | ASTM D 130 |

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

03.2021.03.23



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr