

LUBEX MITRAS ATF M15

HIGH PERFORMANCE AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION

It is a high performance automatic transmission fluid produced by blending synthetic base oils and high technology additives.

APPLICATION/USAGE

LUBEX MITRAS ATF M15 is an automatic transmission fluid designed for the new generation Mercedes-Benz 7-speed and 7-G Tronic Plus models. This product may only be mixed with other officially approved MB 236.15 automatic transmission fluids and is not compatible with previous Mercedes-Benz automatic transmission fluids.

ADVANTAGES/BENEFITS

- It provides significant fuel economy due to having the lowest viscosity value among the previous ATFs.
- With the help of its high pumpability and circulation performance even at the lowest temperatures, it prevents transmission wear during cold start-up conditions.
- By its extremely low friction property it provides smooth and vibration-free driving comfort. It is a long-life transmission fluid that delivers superior performance even in extreme driving conditions with exceptional thermal stability and oxidation resistance.

- It protects transmission against wear by building a superior oil film in all climate conditions, results extending the life of the transmission.
- It prevents oil leakage and increases the efficiency and reliability of the transmission. Prevents the formation of deposit with high-tech additives, does not make foam and provides protection against rust and corrosion.

SPECIFICATIONS/APPROVALS

MB 236.15

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METODU
Appearance	Blue - Bright	-
Density (15°C, g/cm ³)	0,84	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	4,3	ASTM D 445
Viscosity Index	168	ASTM D 2270
Flash Point (°C)	185	ASTM D 92
Pour Point (°C)	-45	ASTM D 97
Foam (93,5°C, Seq. II, ml, max.)	50/0	ASTM D 892
Brookfield Viscosity (-40°C, mPa.s)	4500	ASTM D 2983
Cupper Corrosion (3 h, 100°C, max.)	1b	ASTM D 130

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2021 03.23



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr