

LUBEX MITRAS MT EP SYN 75W

HIGH PERFORMANCE FULLY SYNTHETIC MANUAL TRANSMISSION OIL

PRODUCT DESCRIPTION

Lubex Mitras MT EP SYN 75W is a high-performance manual transmission oil that is developed by using specially selected synthetic base oils and superior additive technology.

- Its high oxidation and thermal stability prevents sludge formation and enables meeting long service interval requirements.
- High shear stability improves lubrication efficiency and extends the life of the equipment.

APPLICATION / USAGE

Lubex Mitras MT EP SYN 75W is suitable for use in manual transmissions of the passenger and light duty vehicles of many different brands (such as Abarth, Alfa Romeo, Audi, Baic, BMW, BYD, Chevrolet, Chrysler, Citroen, Dacia, Daihatsu, Dodge, Dongfeng Xiaokang, DS, Fiat, Ford, GAC, Haima, Hyundai, Infiniti, Jeep, Land Rover, Mazda, Mini, Mitsubishi, Nissan, Opel, Peugeot, Renault, Saab, Seat, Skoda, Subaru, Suzuki, Tata, Toyota, UAZ, Vauxhall, Volkswagen and Volvo) where API GL-4 performance level is required.

SPECIFICATIONS / APPROVALS

API GL-4

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

ADVANTAGES / BENEFITS

- It offers perfect comfort during gear shifting with its superior friction characteristics and synchromesh compatibility.
- Low viscosity feature provides fuel economy without compromising its anti-wear performance even under difficult driving conditions.
- Its excellent fluidity characteristic at low temperatures provides smooth gear shifting and superior protection during cold driving conditions.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Grade	75W	-
Appearance	Clear, Yellow	-
Density (20°C, g/cm ³)	0,839	ASTM D 1298
Kinematic Viscosity (40°C, cSt)	37,01	ASTM D 445
Kinematic Viscosity (100°C, cSt)	7,173	ASTM D 445
Viscosity Index	161	ASTM D 2270
Flash Point (°C, min)	219	ASTM D 92
Pour Point (°C)	-51	ASTM D 97
Brookfield Viscosity @ -40°C, mPa.s	11842	ASTM D 2983

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2023.11.13



BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr