

LUBEX PRIMUS MDA-LA 0W-30

HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

It is a high-performance synthetic engine oil suitable for use in gasoline, diesel and CNG (compressed natural gas) passenger and commercial vehicles, produced with specially selected fully synthetic base oils and additive technology.

APPLICATION/ USAGE

It was developed especially for use in CNG (compressed natural gas) Mercedes-Benz OM936G Euro 6 engines where MB 229.61 specification is required. It is also suitable for use in new generation passenger and light commercial vehicles that require Ford WSS-M2C950-A and Opel Vauxhall OV 040 1547-G30 specifications. It can also be recommended for vehicles with particulate filters where ACEA C2 performance class engine oil must be used.

ADVANTAGES/ BENEFITS

- Even at coldest start-up conditions it prevents metal-metal contact and minimize wear by building a stable oil film with its excellent flow performance.
- Owing to its low viscosity characteristic and low friction feature, it helps to achieve lower emission by providing fuel economy.
- It extends engine life by providing excellent protection against deposit and soot formation with its superior cleaning performance.
- It is produced with mid-SAPS (sulfated ash, phosphorus and sulfur) technology for engines with particulate filter (PF) to reduce harmful exhaust emissions. It extends the life of the exhaust emission system and protects the environment.

- It protects the engine against corrosion thanks to its specially selected additives by neutralizing the acidic compounds formed as a result of combustion.
- Its high oxidation and thermal stability enable to prevent the formation of deposits in the engine and provide superior protection without compromising lubrication performance during the long oil change interval.

SPECIFICATIONS/ APPROVALS

API SP, SN PLUS
ACEA C2; A5/B5
ILSAC GF-6A
Ford WSS-M2C950-A
MB-Approval 229.61; MB 227.61
Opel Vauxhall OV 040 1547 -G30

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5) - (+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	0W-30	-
Density (20°C, g/cm ³)	0.836	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	9.77	ASTM D 445
Viscosity Index	180	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-45	ASTM D 97
TBN (mgKOH/g)	9.5	ASTM D 2896
CCS (-35°C, cP)	5650	ASTM D 5293
HTHS (150°C, cP)	2.9	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2024.12.23

BELGİN

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr