

LUBEX PRIMUS MV 10W-40**HIGH PERFORMANCE SYNTHETIC MOTOR OIL****PRODUCT DESCRIPTION**

Synthetic technology motor oil specially developed to provide superior protection against wear, corrosion and sludge formation, enabling sustainable performance for today's modern engines and challenging driving conditions.

APPLICATION/ USAGE

Lubex Primus MV 10W-40 is suitable for use in gasoline, LPG and light commercial diesel engines where the manufacturer recommends an ACEA A3/B4, API SP or earlier specification SAE 10W-40 motor oil. It is also recommended for use in vehicles requiring MB 229.3, Renault RN0700 / RN0710, VW 501.00 / 505.00 and PSA B71 2300 specifications.

ADVANTAGES/ BENEFITS

- Displays excellent lubrication performance at high and cold temperature climate conditions in all seasons.
- Protects the engine against wear during all severe driving conditions.
- Provides superior protection against high temperature deposit and sludge formation and keeps the engine clean that help to extend the life of it.
- Its improved viscosity characteristics enables to build-up a durable oil film on the critical engine components and minimize wear.

- Its excellent oxidation and thermal stability provide advanced resistance to viscosity thickening and offers reliable lubrication performance throughout long service intervals.

SPECIFICATIONS/ APPROVALS

API SP
ACEA A3/B4
MB 229.3
VW 501 00 / VW 505 00
Renault RN 700 / RN 710
PSA B71 2300

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5) / (+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-40	-
Density (15°C, g/cm3)	0.870	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14.4	ASTM D 445
Viscosity Index	149	ASTM D 2270
Flash Point (°C)	220	ASTM D 92
Pour Point (°C)	-30	ASTM D 97
TBN (mgKOH/g)	10.3	ASTM D 2896
CCS (-25°C, cP)	6500	ASTM D 5293
HTHS (150°C, cP)	4.3	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

05.2025.03.14

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr