

LUBEX PRIMUS MV 10W-60**FULLY SYNTHETIC MOTOR OIL FOR HIGH PERFORMANCE VEHICLES****PRODUCT DESCRIPTION**

Fully synthetic motor oil developed with high-performance synthetic base oils and superior additive technology especially for use in high-speed motor sports vehicles.

APPLICATION/ USAGE

Lubex Primus MV 10W-60 can be used in gasoline, diesel (without particulate filter) and LPG vehicles where the equipment manufacturer recommends SAE 10W-60 motor oil meeting ACEA A3/B4, API SP or earlier specifications. It is particularly recommended for use in motorsport vehicles where the oil temperature is high.

ADVANTAGES/ BENEFITS

- Excellent viscosity stability at high operating temperatures provides superior lubrication performance throughout service intervals.
- Provides extra protection by building an excellent oil film in high-speed motor sports vehicles and high mileage old vehicles.
- Thicker fluidity characteristic of SAE 10W-60 provides extra benefit for reducing oil consumption especially in high mileage older vehicles.
- Provides superior protection against oxidation-induced viscosity thickening and wear in all driving and road conditions.

- Its high-performance detergent-dispersant additives prevent the accumulation of soot and deposits resulting from combustion in the critical components of the engine and lubrication channels, ensuring the engine remains clean.

SPECIFICATIONS/ APPROVALS

API SP
ACEA A3/B4
VW 501 00 / VW 505 00
Renault RN 700 / RN 710
PSA B71 2300

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5) - (+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	10W-60	-
Density (15°C, g/cm3)	0.854	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	24.0	ASTM D 445
Viscosity Index	165	ASTM D 2270
Flash Point (°C)	235	ASTM D 92
Pour Point (°C)	-30	ASTM D 97
TBN (mgKOH/g)	10.3	ASTM D 2896
CCS (-25°C, cP)	5700	ASTM D 5293
HTHS (150°C, cP)	5.8	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2025.03.20

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr