

LUBEX PRIMUS EC PLUS 5W-20
HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL**PRODUCT DESCRIPTION**

It is a high-performance fully synthetic motor oil formulated by using specially selected base oils and new generation additive technology.

APPLICATION / USAGE

It has been developed specifically to meet the engine oil specifications of gasoline vehicles and classified in the SQ-RC category by the American Petroleum Institute (API). It also meets the requirements of ILSAC GF-7A and Ford, GM, Chrysler and Fiat specifications. It is suitable for use in gasoline and LPG vehicles.

ADVANTAGES / BENEFITS

- Its excellent resistance to LSPI (Low Speed Pre-Ignition) formation, especially detected in new generation turbo-charged direct injection gasoline engines, prevents possible serious damage and extends engine life.
 - Outstanding viscosity stability minimizes wear that may occur during engine initial start-up even at the lowest temperatures.
 - Its advanced detergent and dispersant property prevent the accumulation of residue and soot resulting from combustion to ensure that the critical engine components and lubrication channels remain clean.
 - Low viscosity characteristics and low friction properties provide fuel economy to reduce CO₂ emissions and protect the environment.
- Improved oxidation and thermal stability provide enhanced protection against deposit formation in the piston and turbocharger at high operating temperatures.
 - Special additive technology protects the engine against rust and corrosion, extends its life and improves operational efficiency.

SPECIFICATIONS / APPROVALS

API SQ-RC
ILSAC GF-7A
GM Dexos1 Gen2
GM 6094M
Ford WSS M2C960-A1
Chrysler MS 6395
Fiat 9.55535 CR 1

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5 °C) - (+40 °C).

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Grade	5W-20	–
Kinematic Viscosity (100°C, cSt)	8.2	ASTM D 445
Viscosity Index	156	ASTM D 2270
Flash Point (°C)	205	ASTM D 92
Pour Point (°C)	-39	ASTM D 97
TBN (mgKOH/g)	7.2	ASTM D 2896

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

01.2025.08.07

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr