

LUBEX PRIMUS MV 5W-30**HIGH PERFORMANCE FULLY SYNTHETIC MOTOR OIL****PRODUCT DESCRIPTION**

High-performance fully synthetic engine oil developed with specially selected synthetic base oils and additive technology, is suitable for use in many different passenger and light commercial vehicles.

APPLICATION/ USAGE

Lubex Primus MV 5W-30 can be used in gasoline, diesel (without particulate filter) and LPG vehicles where the manufacturer recommends SAE 5W-30 engine oil meeting ACEA A3/B4, API SP or earlier specifications. It is also recommended for use in vehicles requiring one of MB 229.5, MB 229.3, Renault RN 0700/0710 and VW 502.00/505.00 specifications.

ADVANTAGES/ BENEFITS

- Its excellent fluidity performance minimizes the wear that may occur during cold start-up of the engine especially at low operating temperatures.
- High performance detergent-dispersant additives prevent the accumulation of deposit and soot resulting from combustion, ensuring the lubrication channels and critical components remain clean and increasing the operating efficiency of the engine.
- Its superior oxidation and thermal stability provide excellent resistance to ageing and deterioration, enabling excellent lubrication performance throughout the service intervals recommended by vehicle manufacturers.

- Specially selected additives in its formulation protect the engine against corrosion and wear by neutralizing the acidic components released as a result of combustion.
- Advanced viscosity control ensures the formation of a reliable oil film at high pressures and high operating temperatures, improving engine performance.

SPECIFICATIONS/ APPROVALS

API SP
ACEA A3/B4
MB 229.3
MB-Approval 229.5
VW 502 00 / VW 505 00
Renault RN 700 / RN 710

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5) / (+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	5W-30	-
Density (15°C, g/cm ³)	0.85	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	11.7	ASTM D 445
Viscosity Index	158	ASTM D 2270
Flash Point (°C)	210	ASTM D 92
Pour Point (°C)	-39	ASTM D 97
TBN (mgKOH/g)	10.3	ASTM D 2896
CCS (-30°C, cP)	6200	ASTM D 5293
HTHS (150°C, cP)	3.5	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

05.2025.07.31

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr