

LUBEX ROBUS TURBO 15W-40**HIGH PERFORMANCE DIESEL MOTOR OIL****PRODUCT DESCRIPTION**

It is heavy duty diesel engine oil that is formulated with high quality mineral base oils and special additive technology and it has wide usage in old model trucks, buses, trucks, construction machines, agricultural machines and generators.

APPLICATION/ USAGE

It is used for naturally aspirated or medium-speed, turbo and supercharged motors and heavy-duty motors such as trucks, buses, heavy construction equipment, agricultural machinery etc. and commercial vehicles. It is suitable for using in diesel motors of light/medium heavy vehicles that are worked long distance transport.

ADVANTAGES/ BENEFITS

- Provides constant lubrication in any road and climate conditions. Therefore, it can be safely used in four seasons,
- Prevents wear and corrosion, provides excellent motor protection,
- Creates a durable oil film at any temperature, minimizing wear during engine start-up and heating.
- Helps reduce maintenance costs on multi-mileage vehicles.
- Provides superior protection in critical parts of the engine with improved cleaning performance.

- With the help of the detergent-dispersant additives it contains, it prevents the accumulation of sediment by dispersing the dirt formed as a result of combustion. This ensures that the lubrication channels are constantly clean. Improves engine performance and extends life.
- Increases engine performance by providing maximum efficiency from fuel.

SPECIFICATIONS/ APPROVALS

API CF-4, CF
ACEA E2, A2/B2
MAN M 271
MB 228.1

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Class	15W-40	-
Density (15°C, g/cm ³)	0.886	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	13.9	ASTM D 445
Viscosity Index	130	ASTM D 2270
Flash Point (°C)	225	ASTM D 92
Pour Point (°C)	-24	ASTM D 97
TBN (mgKOH/g)	10.0	ASTM D 2896
CCS (-20°C, cP)	6600	ASTM D 5293
HTHS (150°C, cP)	3.7	ASTM D 4741

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

04.2024.10.18

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr