

LUBEX ROBUS MASTER PLUS 10W-40**HIGH PERFORMANCE FULLY SYNTHETIC DIESEL MOTOR OIL****PRODUCT DESCRIPTION**

It is a high performance fully synthetic heavy duty diesel engine oil blended by using specially selected synthetic base oils and advanced additive technology for use in all severe climate and driving conditions.

APPLICATION/ USAGE

It has been developed for use in primarily Scania and many different brands Euro V and Euro IV heavy duty diesel vehicles using low or high sulphur fuel. It can be recommended in Euro III, Euro II and Euro I vehicles and also for use in the retarder systems of some vehicles.

ADVANTAGES/ BENEFITS

- Its advanced viscosity stability provides outstanding protection in all seasons without compromising lubrication performance in all climate and road conditions.
- Its superior detergent and dispersant properties prevent deposits and soot accumulation, ensuring that the critical parts and lubrication channels of the engine remain clean and extend engine life.
- Its high oxidation and thermal stability provides excellent protection against sludge and deposit formation throughout the extended service interval resulting increased lubrication efficiency.
- It extends engine life and saves maintenance costs by protecting against wear that may occur during engine start-up even at the lowest ambient temperatures.

SPECIFICATIONS/ APPROVALS

API CI-4
ACEA E7, E4
CES 20078-77
DEUTZ DQC IV-18
MTU TYPE 3
MACK EO-N
MAN M 3277
DTFR 15B120
DTFR 13D110
RENAULT RXD, RLD-2
SCANIA LDF-3
VOLVO VDS-3
VOITH RETARDER Class B

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	TYPICAL VALUES	TEST METHOD
SAE Viscosity Grade	10W-40	-
Density (15°C) (g/cm ³)	0.869	ASTM D 4052
Kinematic Viscosity (100°C, cSt)	14.9	ASTM D 445
Viscosity Index	150	ASTM D 2270
Flash Point (°C)	>225	ASTM D 92
Pour Point (°C)	-36	ASTM D 97
TBN (mgKOH/g)	15.4	ASTM D 2896
CCS (-25°C, cP)	6500	ASTM D 5293

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."

00.2025.03.14

**BELGİN**

BELGİN MADENİ YAĞLAR TİC. ve SAN. A.Ş.
Gebze OSB Mah. İhsan Dede Cad.
No: 125/1, 41400 Gebze, Kocaeli, Turkey
T +90 262 751 02 92 F +90 262 751 01 98
info@lubex.com.tr - lubex.com.tr