

# **LUBEX RAPIDUS 4T SCOOTER 10W-40**

## FOUR STROKE SCOOTER MOTORCYCLE OIL

## PRODUCT DESCRIPTION

It is a high performance four-stroke scooter motorcycle oil developed using high quality mineral and synthetic oils and a special additive package.

#### **APPLICATION/ USAGE**

It is suitable for use in 4-stroke scooters and maxiscooters that are exposed to harsh operating conditions, especially in daily driving conditions with heavy stop-and-go traffic.

#### **ADVANTAGES/ BENEFITS**

- High shear stability ensures reliable and uninterrupted lubrication performance by keeping viscosity changes at a minimum level throughout the oil change interval.
- Its superior oxidation and thermal stability provide excellent protection against sludge, keeping the engine clean and extending its life.
- It protects the engine against wear during start-up and harsh driving conditions by forming a durable oil film in all climatic conditions.
- Its detergent-dispersant additives help to clean soot and sludge formed during combustion and prolongs the engine life.

• Its special formulation provides low oil evaporation that helps to reduce the oil consumption.

#### SPECIFICATIONS/ APPROVALS

API SI

JASO MB

## **STORAGE**

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

#### **HEALTH AND SAFETY**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

| TECHNICAL PROPERTIES             | TYPICAL VALUES | TEST METHOD |
|----------------------------------|----------------|-------------|
| SAE Viscosity Class              | 10W-40         | -           |
| Kinematic Viscosity (100°C, cSt) | 14.0           | ASTM D 445  |
| Viscosity Index                  | 150            | ASTM D 2270 |
| Flash Point (°C)                 | 220            | ASTM D 92   |
| Pour Point (°C)                  | -27            | ASTM D 97   |
| TBN (mgKOH/g)                    | 6.5            | ASTM D 2896 |

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."





# BELGIN